



OLYMPIAN-PADS & OLYMPIAN-TILE

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1 Proprietary Products: Olympian-Pad or Olympian-Tile Sports Flooring designed for use in weight-rooms, fitness areas, locker rooms, ice arena perimeter flooring or anywhere tough commercial flooring is needed.

1.2 Manufacturer:

Amarco Product / American Mat & Rubber ,LLC

5 Powder Horn Drive

Warren, NJ 07059

Phone: (866)688-6287

(732) 302-1122

Fax: (732) 302-1120

Web: www.amarcoproducts.com

E-mail: info@amarcoproducts.com

1.3 Proprietary Product Description

1.3.1 Product Manufacture Process: Amarco Products Olympian-Pad or Olympian-Tile are manufactured from recycled truck tire rubber buffings that Amarco then re-grinds and sifts. The buffings are then vulcanized under heat and pressure to produce a solid mat. This process creates a rubber mat that offers high value for tensile strength as well as tear and abrasion resistance.

1.3.2 **Olympian-Pad** options:

3/8" (10mm) thick, 4 ft (1.2m) by 6 ft

(1.8m) slabs; 55 lbs (25 kg) non-bevel only

1/2" (13mm) thick, 4 ft (1.2m) by 6 ft

(1.8m) slabs; 73 lbs (34 kg) non bevel only

3/4" (19mm) thick, 4 ft (1.2m) by 6 ft

(1.8m) slabs; 105 lbs (47 kg) non bevel only.

NOTE: Due to molding process, 4 ft by 6 ft mat sizes may vary slightly. If using these mats to cover an area, the mats will have to be "trued" to achieve completely straight edges.

Olympian-Tile Interlock System

3/8" (10mm) thick; 4 ft (1.2m) by 4 ft(1.2m) Approximately 36 lbs (16.3kg) Center, Border, and Corner interlocking pieces. Also, 2 ft (.6m) by 4 ft (1.2m) Approx 16 lbs (7.3kg) and 2 ft(.6m) by 2 ft (.6m) approx 8 lbs (3.6kg) Border and Corner interlocking pieces.

1/2" (13mm) thick; 4 ft (1.2m) by 4 ft(1.2m) approx 45 lbs (20.4kg) Center, Border and Corner interlocking pieces. Also 2 ft (.6m) by 4 ft (1.2m) approx 22 lbs (10kg) and 2 ft (.6m) by 2 ft (.6m) approx 11 lbs (5kg) Border and Corner interlocking pieces. Both 3/8" and 1/2" pieces above are available in Bevel or Non-Bevel edges. 3/4" (19mm) thick; 3 ft (.9m) by 4 ft (1.2m) Approx 49 lbs (22.2kg) Center interlocking pieces. 2 ft (.6m) by 3 ft (.9m) approx 24 lbs

(10.9kg) and 2 ft (.6m) by 4 ft (1.2m) approx 33lbs (15kg) Border interlocking pieces. 2 ft (.6m) by 2 ft (.6m) approx 16 lbs (7.3kg) Corner interlocking pieces. Available in Bevel or Non-Bevel edges. Amarco has in house CAD/Engineering operation to calculate size and number of pieces needed to cover any area. Over 500 layouts already programed and ready to cut. Layout drawings available upon request.

1.4 Manufacturer Product Recommendations: Both Olympian-Pad or Olympian-Tile are intended to be a loose lay product, no adhesive is necessary. Amarco Mats and Flooring are not recommended for applications where there is prolonged exposure to direct sunlight (UV) as this will harden the mats over time. It is also not recommended that mats are exposed to any petroleum based products as those will deteriorate rubber.

2. PRODUCT TECHNICAL DATA

2.1 Original Compression-Deflection Results

@20 PSI 5%

@50 PSI 10%

@150 PSI 20%

@750 PSI 50%

Olympian-Pad or Olympian-Tile Product Specification

Amarco Products

Product Specification

2.2 Thickness Tolerance

3/8" Mats - + .035

1/2" Mats - + .040

3/4" Mats - + .045

2.3 **Mat Bevels:** 30 degrees truncated

2.4 **Specific Gravity:** (H₂O=1) 1.12

2.5 **Density:** LBS/CU FT = 70

2.6 **R Value:** 1/BTU/HR/SQFT/IN/Deg Fahrenheit=1

2.7 **Recycled Content:** 94%

2.8 Environmental & Chemical:

Abrasion, Creep, Impact, Resistivity

GOOD

Vibration, Sound, Oxidation, Alcohol

GOOD

Water, Insulation, Bacterial Growth

GOOD

Mild Acids and Alkalines

GOOD

Tear, Steam, Weather, Animal/Veg oils

FAIR

Concentrated Acids and Alkalines

FAIR

Ozone, Gasoline, Aromatic Hydrocarbons

POOR

Spike/Skate Traffic

VERY GOOD

2.9 Physical Properties

Durometer-Shore A (ASTM D-2240) 63

Tensile Strength (ASTM D-412) 800

Elongation % (ASTM D-412) 275
Tear Resistance (ASTM D-624) 135
Coefficient of Friction (ASTM C1028) 0.85 dry 0.95 wet
Taber Abrasion (ASTM C-501) 1000, CY, MG 300
Flame Resistance (UL94HB) PASS
Flame Resistance (MIL-M15562F) PASS
Coefficient of Expansion-IN/IN/Deg Fahrenheit 0.00012
Recycled Rubber Purity - %99.5
Durometer Tolerance 60-65

3. INSTALLATION

3.1 The installation of

Olympian-Pad or Olympian-Tile should not begin until all other construction is completed, especially overhead work and drywall work. If mats or flooring are being placed on newly poured concrete, the concrete must be sealed prior to laying mats down. Subsurface must be smooth, flat and free of all foreign material. Mats should be placed in the area of installation for 24 hours prior to laying them down to make sure they are at same temperature. Written installation instructions are available upon request or found on Amarco website.

3.2 Olympia Flooring installations:

- a. If the wall layout contains borders on 2 sides perpendicular to each other, lay those first.
- b. Fill in rows and columns of center pieces until you get the other two walls.
- c. Trim to fit.

Note: when Amarco mats are installed, the diamond surface needs to be on top.

How to trim the sides:

- a. The mats are easy to cut. A good utility knife with a sharp blade, a jigsaw, or a reciprocating saw all work well.
- b. A good tip is to have silicone or non petroleum lubricant handy, keeping the blade lubricated will aid in cutting. Be sure to take proper safety precautions when cutting.
- c. Another helpful tip is to place a wooden 2 x 4 under the mat along the line of the intended cut creating an arch. Cutting along this arch, the mat will have a tendency to split and pull apart more easily as the knife is pulled through the mat.

2011 Amarco Products

Product Specification

Olympian Island:

This type of installation does not require the use of tools. Just fit pieces together. For reference a 31'1" x 29'9" island can be done in 1.5 hours.

3.2 Olympian Sport installations:

Start from a straight edge wall and work your way across the room. These mats just butt up next to each other. Due to the molding process mats are not always perfectly rectangular, some trimming is required, please follow the cutting instructions stated previously. Amarco has ability to "true" edges of Olympian Sport mats upon request for an extra charge.

4. AVAILABILITY

4.1 Available through authorized Amarco dealers and distributors both nationally and internationally.

5. WARRANTY

5.1 Amarco Products guarantees its Olympian Sport rubber flooring for a period of three (3) years against deterioration due to faulty materials or workmanship. This Guarantee does not cover damage that could occur from other abuses beyond the general intended application of

the product; no does it cover damage or deterioration caused by the use of adhesives. No other warranty is expressed or implied. Limit of liability from any losses resulting from the use of this product shall be for the purchase only, and applied in the form of a credit, excluding any freight charges.

6. CLEANING AND MAINTENANCE

6.1 Amarco mats are easy to keep clean and maintain since, in most cases, sweeping or vacuuming is all that is required to keep the mats clean. A "beater brush" vacuum works best. More stubborn dirt and grime can be removed with warm water and a mild cleaner. A mild solution of Dawn's Dishwashing Liquid and water works extremely well. When the mats are new, and if the room has less than adequate ventilation, there can be instances when sensitive noses will notice a rubber smell. Cleaning the mats soon after installation goes a long way towards reducing this odor. We've been told that scented Pinesol works very well in this regard. There is still no substitute for proper ventilation however. Whatever the cleaner used however, it is important to make sure all the cleaner residue is mopped up thoroughly. Cleaners containing a wax agent are not recommended, as the wax can cause build up. Caution: Oil, grease, and solvents should not be left on the mats for extended periods of time. Wipe off as soon as possible and clean any residue with soap and water. DO NOT use petroleum-based cleaners on the mats, as these can cause deterioration.

AMARCO PRODUCTS
5 Powder Horn Drive
Warren, NJ 07059
Phone: 1-732-302-1122
Fax: 1-732-302-1120

2011 Amarco Products