



Products: Linear-Tile, Matrix Tile

INSTALLATION

Use plumb lines to lay out tile pattern. Lay out tile pattern from center of room such that tiles at perimeter are wider than 6 inches. Install tiles in decorative patterns using different colors, if applicable, as shown on drawings and approved shop drawings. Scribe tile to walls and other vertical appurtenances to produce tight joints. When cutting, use a power saw to create clean, straight edges. Interlock tiles by forcing male tabs into female receptacles, using rubber mallet or similar tool to assemble. Ensure tightness. Interlock edge ramps with tiles using male tabs and female receptacles. At corners, provide corner ramp sections.

CLEANING AND MAINTENANCE

DAILY: Vacuum clean, mop. Tiles can be mopped or scrubbed with a scrub brush. They can also be hosed down with a garden or commercial power washer and can be washed with a commercial detergent such as Spic-N-Span. Do not wax or use equipment to wash tiles that have been in contact with wax.

WARRANTY

Limited 5-Year Warranty on Tile, 3-Year Warranty on carpet inserts. Amarco Products provides a limited, pro-rated 5-year warranty from date of shipment on Linear Tile that shall be free from defects in material and workmanship. The carpet inserts have a pro-rated 3-year warranty for normal use where the carpet wears down below surface. The company's obligation under this warranty is limited to replacement if any defective material that is proved to the company, in their sole discretion, to be defective, within the warranty period. The company's obligations do not include transportation costs or the costs of installing any material that is replaced, and the buyer shall be solely responsible for such costs. Any material that is replaced under this warranty will be pro-rated from the original ship date.

Questions? Please call Amarco Products. for assistance.

Amarco Products 5 Powder Horn Drive, Warren, NJ 07059

• 1-866-688-6287 • Fax: 1-732-302-1120

• www.amarcoproducts.com