


AT-800 AL-TRACK

Nylon Carpet Insert




Features:


- Extruded aluminum treads alloy 6063-T52
- Continuous vinyl cushion for superior noise reduction
- Roll-Up for easy cleaning of recess
- Optional perforated hinge for added drainage
- Single section width to 144" (3658)
- 100% solution dyed nylon fiber with 1/4" (6) finish pile height, 33.8 oz/sq yd in rigid backing
- Static Coefficient of Friction (ASTM D-2047-82)
Dry: 0.48, Wet: 0.67

Optional Framing:


*** Amarco requires that exact opening dimensions be provided. Factory will fabricate mats 1/4" (6) smaller than exact opening dimensions to allow for proper fit.**



Recessed frame ATF-1002 (see ED.1.0)
or MRF-1005 (see ED.2.0)



Recessed frame ATF-125 (see ED.3.0)




Surface frame ATF-225 (see ED.4.0)

Hinge Details:



Ball & Socket Hinge



Optional perforated hinge
(solid hinge standard)

Optional Nosings:



Square vinyl nosing (see ED.20.0)




Beveled vinyl nosing (see ED.21.0)

Finishes:

- Aluminum tread and spacer:
Mill finish (standard) #405
Medium bronze anodized #404
Clear anodized #403
Black anodized #462
- Vinyl cushion: Black
- Rigid-Back Nylon carpet insert:
Manufacturer's standard colors

Sectioning information:



*** Mats over 66 square feet may require sectioning as determined by the factory**

Amarco reserves the right to discontinue a design or modify an existing design without prior notice

Customer :	Project :	ED.14.0d
Architect :	Sales Rep :	