



## AT-250 - 3/4" Aluminum Roll-Up Grating w/ Aluminum Abrasive Insert




### Optional Framing:

\* Amaro Products requires that exact opening dimensions be provided. Factory will fabricate mats 1/4" (6) smaller than exact opening dimensions to allow for proper fit on dimensions without nosing.



### Hinge Detail:




### Features:

- Extruded aluminum treads alloy 6105-T5
- Continuous vinyl cushion for superior noise reduction
- 3/4" (19) deep for increased drainage ability
- Perforated hinge for added drainage
- Single section width to 144" (3658)
- Aluminum abrasive insert: Extruded aluminum base with applied abrasive strip
- Static Coefficient of Friction (ASTM D-2047-82)
  - Dry: > 1.14, Wet: > 1.20

### Finishes:

- Aluminum tread:
  - Mill finish (standard) #405
  - Medium bronze anodized #404
  - Clear anodized #403
  - Black anodized #462
- Aluminum abrasive insert alloy 6105-T5:
  - Mill finish aluminum base (standard) #405
  - Abrasive from manufacturer's color samples

### Sectioning information:




\* Mats over 48 square feet may require sectioning as determined by the factory

Amarco Products reserves the right to discontinue a design or modify an existing design without prior notice

Customer :	Project :	
Architect :	Sales Rep :	


# AT-250 - 3/4" Aluminum Roll-Up Grating w/ Nylon Carpet Insert




## Optional Framing:

## Note On Dimensions:

Amarco Products requires that exact opening dimensions be provided. Factory will fabricate mats 1/4" (6) smaller than exact opening dimensions to allow for proper fit on dimensions without nosing.



## Hinge Detail:




## Features:

- Extruded aluminum treads alloy 6105-T5
- Continuous vinyl cushion for superior noise reduction
- 11/16" (17) deep for increased drainage ability
- Roll-Up for easy cleaning of recess
- Perforated hinge for added drainage
- Single section width to 144" (36568)
- 100% solution dyed nylon fiber with 1/4" (6) finish pile height, 33.8 oz/sq yd in rigid backing
- Static Coefficient of Friction (ASTM D-2047-82)  
Dry: 0.48, Wet: 0.67

## Finishes:

- Aluminum tread:
  - Mill finish (standard) #405
  - Medium bronze anodized #404
  - Clear anodized #403
  - Black anodized #462
- Rigid-Back Nylon carpet insert:
  - Select from manufacturer's color samples

## Sectioning information:



\* Mats over 48 square feet may require sectioning as determined by the factory

Amarco Products reserves the right to discontinue a design or modify an existing design without prior notice


Customer :

Project :

Architect :


Sales Rep :

# AT-250 Aluminum Roll-Up Grating w/ Rigid Corrugated Vinyl Insert




## Optional Framing:

\* Amaro Products requires that exact opening dimensions be provided. Factory will fabricate mats 1/4" (6) smaller than exact opening dimensions to allow for proper fit on dimensions without nosing.



## Hinge Detail:




## Features:

- Extruded aluminum treads alloy 6105-T5
- Continuous vinyl cushion for superior noise reduction
- 3/4" (19) deep for increased drainage ability
- Perforated hinge for added drainage
- Single section width to 144" (3568)

## Finishes:

- Aluminum tread:
  - Mill finish (standard) #405
  - Medium bronze anodized #404
  - Clear anodized #403
  - Black anodized #462
- Rigid corrugated vinyl insert (colorable):
  - Select from manufacturer's color samples

## Sectioning information:



\* Mats over 48 square feet may require sectioning as determined by the factory


Customer :

Architect :

Project :

Sales Rep :


# AT-250 Aluminum Roll-Up Grating w/ Maxi-Tuft Carpet Insert




## Optional Framing:

### Note On Dimensions:

\* Amaro Products requires that exact opening dimensions be provided. Factory will fabricate mats 1/4" (6) smaller than exact opening dimensions to allow for proper fit on dimensions without nosing.



## Hinge Detail:




## Features:

- Extruded aluminum treads alloy 6105-T5
- Continuous vinyl cushion for superior noise reduction
- 11/16" (17) deep for increased drainage ability
- Roll-Up for easy cleaning of recess
- Perforated hinge for added drainage
- Single section width to 144" (36568)
- Space dyed, 100% polyamide nylon, tetra-lobal fibers, 5/32 (4) pile height, 30 oz/sq yd
- Static Coefficient of Friction (ASTM D-2047-82)  
Dry: 0.49, Wet: 0.77

## Finishes:

- Aluminum tread:
  - Mill finish (standard) #405
  - Medium bronze anodized #404
  - Clear anodized #403
  - Black anodized #462
- Maxi-Tuft long wear carpet insert:
  - Select from manufacturer's color samples

## Sectioning information:



\* Mats over 48 square feet may require sectioning as determined by the factory


Customer :

Architect :

Project :


Sales Rep :

# AT-250 - 3/4" Aluminum Roll-Up Grating w/ Corrugated Aluminum




## Optional Framing:

- \* Amaro Products requires that exact opening dimensions be provided. Factory will fabricate mats 1/4" (6) smaller than exact opening dimensions to allow for proper fit on dimensions without nosing.



## Hinge Detail:




## Features:

- Extruded aluminum treads alloy 6105-T5
- Continuous vinyl cushion for superior noise reduction
- 3/4" (19) deep for increased drainage ability
- Perforated hinge for added drainage
- Single section width to 144" (3568)
- Static Coefficient of Friction (ASTM D-2047-82)  
Dry: 0.61, Wet: 0.92

## Finishes:

- Aluminum tread:  
Mill finish (standard) #405  
Medium bronze anodized #404  
Clear anodized #403  
Black anodized #462
- Corrugated aluminum insert alloy 6105-T5:  
Mill finish (standard) #405

## Sectioning information:



\* Mats over 48 square feet may require sectioning as determined by the factory

Amarco Products reserves the right to discontinue a design or modify an existing design without prior notice


Customer :

Architect :

Project :

Sales Rep :


## AT-250 - 3/4" Aluminum Roll-Up Grating w/ Bristle Filament Insert




### Optional Framing:

### Note On Dimensions:

Amarco Products requires that exact opening dimensions be provided. Factory will fabricate mats 1/4" (6) smaller than exact opening dimensions to allow for proper fit on dimensions without nosing.



### Hinge Detail:




### Features:

- Extruded aluminum treads alloy 6105-T5
- Continuous flexible vinyl cushion for superior noise reduction
- 3/4" (19) deep for increased drainage ability
- Perforated hinge for added drainage
- Single section width to 144" (3658)
- Solution dyed polypropylene fibers, 27 oz/sqyd with 50% Blend 600/12-Denier multi-filament and 595/D1 monofilament. Fibers are fusion bonded to continuous two-ply rigid backing.
- Fibers are waterproof with UV inhibitors for exterior use
- Static Coefficient of Friction (ASTM D2047)  
Dry: 0.64, Wet: 0.67

### Finishes:

- Aluminum tread:  
Mill finish (standard) #405  
Medium bronze anodized #404  
Clear anodized #403  
Black anodized #462
- Vinyl cushion, nosing, and hinge: Black
- Bristle filament carpet insert:  
Manufacturer's standard colors

### Sectioning information:



\* Mats over 48 square feet may require sectioning as determined by the factory

Amarco Products reserves the right to discontinue a design or modify an existing design without prior notice

Customer :


Project :

Architect :

Sales Rep :

# Entrance Mats & Gratings

## ATF-125 Aluminum Frame



### Features:

- Use for AT-800, AT-650, AT-500, or any 3/8" (10mm) - 5/8" (16mm) thick mats
- Extruded aluminum alloy 6063-T5
- Stock length: 12'-3" (3734mm)
- Weight: 0.15 lbs / lf

### Installation Options:

- Surface mounted, mechanically fastened
- Recessed, mechanically fastened
- Mounting hardware spaced at 18" (457mm) on center or as required

### Standard Finishes:

- Mill Finish #405
- Clear anodized #403
- Medium bronze anodized #404
- Black anodized #462

## Entrance Mats & Gratings

# ATF-1002 Aluminum Recessed Frame

