

Diagonal Tile - 3/8" Diagonal Pattern Commercial Walk-Off Tile



Technical Data

PRODUCT COMPOSITION	STANDARD/NORMS	DATA
Manufacturing process	ISO 2424	Needle punched
Pile Yarn Composition	CEE 83/623	100% ASOTA polypropylene fibers
Primary Backing	ISO 2424	Bitumen (Maxphalt)
PRODUCT DIMENSIONS		
Pile Height (+ or - 0.5mm)	ISO 1766	.231 inches
Total Height (+ or - 7.5%)	ISO 1766	.313 inches
Pile Weight (+ or -7.5%)	ISO 8543	37 oz/yd
Total Weight (+ or - 7.5%)	ISO 8543	126 oz/yd
ELECTROSTATIC PROPERTIES		
Dimension Stability	EN 986	Pass
Walk On Test	ISO TR 6356	< 2 KV
COLOR FASTNESS		
To Light	ISO 105 B02	>=6
To Water	ISO 105 E01	5
To Shampoo	BS 1006 UK-TB	5
To Rubbing (dry & wet)	ISO 105 x 12	4-5
FLAMMABILITY RATING		
Pill test (Surface flammability)	ISO 6925 / ASTM D2859 / CPSC FF 1-70	Passes Federal Flammability Standard

Installation

Floor area should be completely clean, dry and free of foreign substances. Use a floor leveler as needed to ensure floor is smooth, even and without cracks. Tiles must be quarter turned when installing. Our matting products can be cut easily to any size, shape or pattern with a utility knife. In glue-down applications, follow adhesive manufacturer's instructions.

Adhesive (if applicable): Amarco Products Multi-Purpose Mat Adhesive, or Approved equal.

Maintenance:

Daily: Vacuum daily with a commercial grade vacuum cleaner that features a rotary power brush or beater bar. Mats release more soil when completely dry.

Periodic Maintenance: Our matting products clean beautifully with the use of a Hot Water Extraction machine. Minimum quarterly intervals recommended for high traffic applications.

For optimum performance during winter months, traffic lanes may require more frequent extraction cleaning depending on weather conditions and climate.

Warranty:

Limited 5-Year Abrasive Warranty. Amarco Products offers a limited warranty for abrasive wear on indoor installations. Warranty requires product installation over a dry, smooth, hard, flat surface free of cracks and foreign substances. Product must be installed using the appropriate Amarco Products brand adhesive or approved equal. Product must be maintained according to maintenance instructions. Failure is defined as the loss of fiber due to abrasive wear of more than Ten (10) percent of the pile-fiber in any given area. This warranty is for abrasive wear only and does not cover burns cuts, gouges, pilling, matting of pile, shedding, flattening of pile or pattern, staining, soiling, oiling, fading nor fiber loss due to abnormal usage. Call Amarco Products for full version of Warranty.