



Foot-Ease - ½" Vinyl Surfaced

Anti-Fatigue Matting

Technical Data

Product Description

- **Materials:** Marbleized surface combined with dense closed cell foam base
- **Thickness:** ½"
- **Mat Sizes:** 2' x 3' / 3' x 5'
- **Roll Sizes:** 2' x 60' / 3' x 60' / 4' x 60'

Criteria	Test	Result
Weight	--	216 oz/yd ²
Tensile Strength	ASTM D412	1000 psi
Tear Strength	MVSS-300	Self Extinguishing
Elongation	ASTM D412	Exceeds 100%
Durometer	ASTM D2240	85-95
Weathering	ASTM D750	7 days - no visual change
Resistance to Chemicals / Fluids		
Acetic Acid		2 - Negligable Effect
Acetone		4 - Not Recommended
Animal Fats		3 - Moderate Effect
Brake Fluid		2 - Negligable Effect
Butyl Alcohol		2 - Negligable Effect
Chlorine Wet		3 - Moderate Effect
Cutting Fluid (wb)		2 - Negligable Effect
Cutting Fluid (so)		3 - Moderate Effect
Diesel Oil		3 - Moderate Effect
Gasoline		2 - Negligable Effect
Mineral Oil		2 - Negligable Effect
Nitric Acid		1 - No Effect
Sodium Hydroxide		2 - Negligable Effect
Sulfuric Acid		1 - No Effect
Toluene		2 - Negligable Effect
Transmission Fluid		3 - Moderate Effect
Trichlorthane		3 - Moderate Effect
Vegetable Oil		2 - Negligable Effect