



## G-1532

### 15/32" Buffed Tire Grating

#### LEED Credits

#### Product Description

- **Divider Material:** ASTM B221
- **Tread Material:** 100% Recycled Tire Tread
- **Binding Material:** Steel wire
- **Thickness:** 15/32"

LEED Category	Credit	Details	Possible Points	Product Detail
Material & Resources (MR)	4	Recycled Content: Post-consumer and ½ Pre-consumer content	1 to 2 possible points	Minimum of 46.4% post-consumer, 41% pre-consumer recycled content
Material & Resources	5	Regional Material: Use building materials or products that have been extracted, harvested or recovered, as well as manufactured, within 500 miles of the project site	1 to 2 possible point	--
Material & Resources	6	Rapidly Renewable Materials: Use rapidly renewable building materials and products for 2.5% of the total value of all building materials and products used in the project, based on cost. Rapidly renewable building materials and products are made from agricultural products that are typically harvested within a 10 year or shorter cycle.	1 possible point	--
Indoor Environmental Quality (IEQ)	4.3	Low-Emitting Materials—Flooring Systems: All carpet installed in the building interior must meet the testing and product requirements of the Carpet and Rug Institute Green Label Plus 1 program. All carpet adhesive must meet the requirements of IEQ Credit 4.1: Adhesives and Sealants, which includes a volatile organic compound (VOC) limit of 50 g/L.	1 possible point	Not applicable. Product does not require adhesives or sealants in the field.
Indoor Environmental Quality (IEQ)	5	Indoor Chemical and Pollutant Source Control: Employ permanent entryway systems at least 10 feet long in the primary direction of travel to capture dirt and particulates entering the building at regularly used exterior entrances. Acceptable entryway systems include permanently installed grilles, grates, and slotted systems that allow for cleaning underneath. Roll-out mats are acceptable only when maintained on a weekly basis by a contracted service organization.	1 possible point	Meets the requirement if the product is installed at least ten (10) feet in the direction of traffic and properly maintained.