



## Park Avenue Tufted Nylon

### Cut-Pile Entrance Mat

#### Technical Data

#### Product Description:

- **Material:** 100% Polyamide Nylon Fibers
- **Backing:** Rubber (6'7" and 13'2" widths); Vinyl (4'3" and 6'7" widths)
- **Roll sizes:** Rubber back: 6'7" x 68' or 13'2" x 68'  
Vinyl back: 4'2" x 82' or 6'7" x 82'

Criteria	Test	Result
Pile Height	ISO 1776	1/4"
Total Height	ISO 1776	Rubber back: 5/16" Vinyl back: 3/8"
Pile Weight	ISO 8543	28.76 oz/yd <sup>2</sup>
Surface Flammability	ASTM D2859 CPSC FF 1-70	Pass
Critical radiant flux	ASTM E648	Class 1
LEED v3 MR Credit 5	Recycled content For 1-2 points: \$ value of all materials = min. average 10% recycled content	10% recycled (post-consumer)
LEED v3 IEQ Credit 4.1	Low-Emitting Materials (Adhesives) For 1 point: low-emitting adhesive with a VOC of 50 g/L or less for indoor carpet adhesive	Rubber back adhesive VOC: 0 g/L
LEED v3 IEQ Credit 5	Indoor Chemical and Pollutant Source Control For 1 point: semi-permanently installed entrance system at least ten feet in length and maintained on a weekly basis by a contracted service organization	LEED acceptable entryway system
LEED v4 Material and Resources (MR)	Sourcing of Raw Materials: For 1 point: products that meet at least one of the responsible extraction criteria for at least 25%, by cost, of the total value of permanently installed building products (Option 2)	Recycled Content: 10% post- consumer
LEED v4 Indoor and Environmental Quality (IEQ)	Low-Emitting Materials (Adhesives): For up to 3 points: threshold emission compliance for the required number of product categories or using the budget calculation method	Green Label Plus Certified
LEED v4 Indoor Environmental Quality (IEQ)	Enhanced Indoor Air Quality Strategies: For 1 point: permanent entryway system that is at least ten feet in length and maintained on a weekly basis	LEED acceptable entryway system