



Prime-Sport Virgin Rubber Rolls

Gym Flooring w/ Underlayment

Technical Data

Product Description

- **Surface Layer Material:** EPDM Virgin Rubber
- **Base Layer Material:** Post-consumer Recycled Rubber
- **Standard Thickness:** 10.5mm
- **Custom Thicknesses:** 7.5mm, 14.4mm, 22.5mm
- **Roll Length:** 48"

Criteria	Test	Result			
		7.5mm	10.5mm	14.5mm	22.5mm
Static Load Limit	ASTM F970	0.004" (@250psi)	0.004" (@250psi)	0.009" (@250psi)	0.025" (250psi)
Coefficient of Friction	ASTM D2047	> 0.9	> 0.9	> 0.9	> 0.8
FloorScore	CA 01350	Certified	Certified	Certified	Certified
Abrasion Resistance	ASTM D3389	< lg, 1,000 cycles	< lg, 1,000 cycles	< lg, 1,000 cycles	< lg, 1,000 cycles
Pill Test	ASTM D2859	Pass	Pass	Pass	Pass
Standard Vertical Deformation	ASTM F2772	.73mm	.5mm	2.66mm	1.6mm
Surface Effect Slip Resistance	ASTM F2772	Pass	Pass	Pass	92
Ball Rebound	ASTM F2772	99.7%	100%	98.8%	100%
Force Reduction	ASTM F2772	12.6%	11.4%	35.7%	38.1%
Impact Insulation Class*	ASTM E492	54	53	58	58
Delta IIC*	ASTM E2179	24	22	27	29