



Sport-Fleck – Custom Recycled Rubber Gym Flooring CSI Specifications

PART 1 GENERAL

1.01 SUMMARY

- A. This Section specifies specialty flooring.
- B. Related Sections: Other Specification Sections which directly relate to the work of this Section include, but are not limited to, the following:
 - 1. Section 03300, Cast-In-Place Concrete; Concrete substrate to receive specialty flooring.

1.02 SUBMITTALS

- A. Product Data: Submit manufacturer's product data and installation instructions. Include methods of installation and requirements for substrate preparation.
- B. Samples: Submit representative samples of each material that is to be exposed in the completed work. Show full color ranges available.
- C. Shop Drawings: Submit shop drawings for approval prior to fabrication. Include detailed plans, required clearances and accessories. Include relationship with adjacent materials.

1.03 DELIVERY, STORAGE, AND HANDLING

- A. Deliver specialty flooring in factory labeled packages. Store and handle in strict compliance with manufacturer's instructions and recommendations. Protect from damage from weather, excessive temperatures, and construction operations.

PART 2 PRODUCTS

2.01 ACCEPTABLE MANUFACTURER

- A. Provide Sport-Fleck Custom Recycled Rubber Gym Flooring by Amarco Products.
5 Powder Horn Dr. Warren, NJ, 07059;
Tel: 866-688-6287. Fax 732-302-1120
www.amarcoproducts.com
info@amarcoproducts.com

2.02 Sport-Fleck Custom Recycled Rubber Gym Flooring

- A. Sports and Fitness Flooring:
 - 1. Product: Sport-Fleck by Amarco Products
 - 2. Materials: Black recycled rubber with EPDM colored granules.
 - 3. Sheet Size: 4 feet wide rolls standard.
 - 4. Edges: Square.
 - 5. Thickness: [5/32" (4mm)] [1/4" (6mm)] [3/8" (9mm)] [1/2" (12 mm)]
 - 6. Color: [Black] [Blue] [Teal] [Orange] [Brick Red] [Purple] [Yellow] [Gold] [Egg Shell] [Beige] [Gray] [Green] [Lipstick] [Raspberry] [Brown] [Beige/Tan] [Blue/Gray] [Blue/Tan] [Gold/Eggshell] [Red/Gray]
Custom Colors available upon request
 - 7. Adhesive: Amarco's CX-941 recommended adhesive for glue-down installation.

PART 3 EXECUTION

3.01 SUBSTRATE PREPARATION

- A. Examine substrates and conditions where specialty flooring will be installed. Do not proceed with installation until unsatisfactory conditions are corrected. Subfloor shall be clean and dry, and within acceptable tolerances.

3.02 INSTALLATION

- A. Strictly comply with manufacturer's installation instructions and recommendations. Coordinate installation with adjacent work to ensure proper clearances and to prevent tripping hazards.
- B. Instruct Owner's personnel in proper maintenance procedures.

3.03 CLEANING AND PROTECTION

- A. Clean exposed surfaces using non-abrasive materials and methods recommended by manufacturer.
- B. Protect specialty flooring until acceptance.

END OF SECTION