



## **Sport-Fleck – Custom Recycled Rubber Gym Flooring CSI Specifications**

### **PART 1 GENERAL**

#### **1.01 SUMMARY**

- A. This Section specifies specialty flooring.
- B. Related Sections: Other Specification Sections which directly relate to the work of this Section include, but are not limited to, the following:
  - 1. Section 03300, Cast-In-Place Concrete; Concrete substrate to receive specialty flooring.

#### **1.02 SUBMITTALS**

- A. Product Data: Submit manufacturer's product data and installation instructions. Include methods of installation and requirements for substrate preparation.
- B. Samples: Submit representative samples of each material that is to be exposed in the completed work. Show full color ranges available.
- C. Shop Drawings: Submit shop drawings for approval prior to fabrication. Include detailed plans, required clearances and accessories. Include relationship with adjacent materials.

#### **1.03 DELIVERY, STORAGE, AND HANDLING**

- A. Deliver specialty flooring in factory labeled packages. Store and handle in strict compliance with manufacturer's instructions and recommendations. Protect from damage from weather, excessive temperatures, and construction operations.

### **PART 2 PRODUCTS**

#### **2.01 ACCEPTABLE MANUFACTURER**

- A. Provide Sport-Fleck Tile by Amarco Products.  
5 Powder Horn Dr. Warren, NJ, 07059;  
Tel: 866-688-6287. Fax 732-302-1120  
[www.amarcoproducts.com](http://www.amarcoproducts.com)  
[info@amarcoproducts.com](mailto:info@amarcoproducts.com)

#### **2.02 Sport-Fleck Custom Recycled Rubber Gym Flooring**

- A. Sports and Fitness Flooring:
  - 1. Product: Sport-Fleck Tile by Amarco Products
  - 2. Materials: Black recycled rubber with EPDM colored granules.
  - 3. Tile Size: 36" x 36"
  - 4. Edges: Square or Interlocking
  - 5. Thickness: [5/32" (4mm)] [1/4" (6mm)] [3/8" (9mm)] [1/2" (12 mm)]
  - 6. Color: [Black] [Blue] [Teal] [Orange] [Brick Red] [Purple] [Yellow] [Gold] [Egg Shell] [Beige] [Gray] [Green] [Lipstick] [Raspberry] [Brown] [Beige/Tan] [Blue/Gray] [Blue/Tan] [Gold/Eggshell] [Red/Gray]  
Custom Colors available upon request
  - 7. Adhesive: Amarco's CX-941 recommended adhesive for glue-down installation.

## **PART 3 EXECUTION**

### **3.01 SUBSTRATE PREPARATION**

- A. Examine substrates and conditions where specialty flooring will be installed. Do not proceed with installation until unsatisfactory conditions are corrected. Subfloor shall be clean and dry, and within acceptable tolerances.

### **3.02 INSTALLATION**

- A. Strictly comply with manufacturer's installation instructions and recommendations. Coordinate installation with adjacent work to ensure proper clearances and to prevent tripping hazards.
- B. Instruct Owner's personnel in proper maintenance procedures.

### **3.03 CLEANING AND PROTECTION**

- A. Clean exposed surfaces using non-abrasive materials and methods recommended by manufacturer.
- B. Protect specialty flooring until acceptance.

END OF SECTION